

Hira FlexiCell XLPE Insulation



R-Value →	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2	2.1	2.2
← Copper Pipe OD (mm) →	12.7	25	25	25	25	25	25	25	25	25	38	38	38	38	38	38	38
	19.1	25	25	25	25	25	25	25	38	38	38	38	38	38	38	38	38
	25.4	25	25	25	25	25	25	38	38	38	38	38	38	38	38	38	38
	31.8	25	25	25	25	25	25	38	38	38	38	38	38	38	38	50	50
	38.1	25	25	25	25	25	25	38	38	38	38	38	38	38	50	50	50
	50.8	25	25	25	25	25	38	38	38	38	38	38	38	38	50	50	50
	63.5	25	25	25	25	25	38	38	38	38	38	38	38	50	50	50	50
	76.2	25	25	25	25	38	38	38	38	38	38	38	50	50	50	50	50
	101.6	25	25	25	25	38	38	38	38	38	38	50	50	50	50	50	55
	127.0	25	25	25	25	38	38	38	38	38	50	50	50	50	50	50	55
	152.4	25	25	25	38	38	38	38	38	38	50	50	50	50	50	50.3	55
	203.2	25	25	25	38	38	38	38	38	50	50	50	50	50	55	55	55
	219.1	25	25	25	38	38	38	38	38	50	50	50	50	50	55	55	63
	254	25	25	25	38	38	38	38	38	50	50	50	50	50	55	55	63
	304.8	25	25	25	38	38	38	38	38	50	50	50	50	50	55	55	63
	355	25	25	25	38	38	38	38	38	50	50	50	50	55	55	63	63
	406	25	25	25	38	38	38	38	38	50	50	50	50	55	55	63	63
457	25	25	25	38	38	38	38	50	50	50	50	50	55	55	63	63	
508	25	25	25	38	38	38	38	50	50	50	50	50	55	55	63	63	

Available as sheet product

Special order only

Values based on k-value 0.032 W/mK in accordance with AS/NZS 4859.1