

## NICHIAS Tombo MG Mighty Cover Rockwool R-Value Chart



R-Value →	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2	2.1	2.2
← Copper Pipe OD (mm) ↑	25	25	25	25	25	25	25	25	25	38	38	38	38	38	38	38	38
12.7	25	25	25	25	25	25	25	25	25	38	38	38	38	38	38	38	38
19.1	25	25	25	25	25	25	25	25	38	38	38	38	38	38	38	38	38
25.4	25	25	25	25	25	25	25	38	38	38	38	38	38	38	38	50	50
31.8	25	25	25	25	25	25	38	38	38	38	38	38	38	38	50	50	50
38.1	25	25	25	25	25	38	38	38	38	38	38	38	38	50	50	50	50
50.8	25	25	25	25	25	38	38	38	38	38	38	38	50	50	50	50	50
63.5	25	25	25	25	38	38	38	38	38	38	50	50	50	50	50	50	50
76.2	25	25	25	25	38	38	38	38	38	50	50	50	50	50	50	50	N/A
101.6	25	25	25	38	38	38	38	38	50	50	50	50	50	50	50	N/A	N/A
127.0	25	25	25	38	38	38	38	38	50	50	50	50	50	N/A	N/A	N/A	N/A
152.4	25	25	25	38	38	38	38	50	50	50	50	N/A	N/A	N/A	N/A	N/A	N/A
203.2	25	25	25	38	38	38	38	50	50	50	N/A						
219.1	25	25	25	38	38	38	50	50	50	N/A							
254	25	25	25	38	38	38	50	50	50	N/A							

Values based on k-value 0.034 W/mK in accordance with AS/NZS 4859.1

InsulShop 2019